

CT202

230 Vac CONTROL UNIT



PLUS

Same programming logic for all control boards CT102B, CT202, CT10224, CT20224 with run inversion via software

Amperometric obstacle detection with run inversion

Standard or programmable slowdown in opening and closing

Programmable automatic partial closing

Separate OPEN - CLOSE inputs and PP - PARTIAL input

Safety edge 8,2Kohm NC - STOP - photo 1 and photo 2

Inputs and safety devices LED visualization

Flashing light output fixed or flashing

LED courtesy light or open gate indicator output

Programmable electro lock timing

Pressure control for hydraulic motors

3 digits display

Optional photo test

Optional test for safety edge

New plug-in radio receiver 4 channels RX4K

MODELS

CODE	DESCRIPTION
CT202	For two motors for swing gate, 230 Vac, with electronic clutch and connector for receiver, slowdown in opening and closing. In box

CT202		
ELECTRICAL DATA		
input power	Vac/Hz	230/50
output power accessories	Vac	24
	Vdc	24
max motor power	W	700+700
max working time	sec	adjustable
max pause time	sec	0 - 900
obstacle detection		yes
GENERIC DATA		
protection degree	IP	54
dimensions (L - D - H)	mm	222 - 110 - 275
operating temperature	°C	-20 + 55